

X-keys® Four, Six, and Eight Button Pendant Switches Specifications

for XK-A-1433-PDT4-R, XK-A-1434-PDT6-R, and XK-A-1435-PDT8-R



- Perfect for use with the X-keys HD15 USB Wire Interface
- Rugged design for Assistive Technology or industrial application
- Uses standard 15 pin extension cable of any length
- Designed for signal level control (not for high voltage or high current)

The X-keys Pendant Switches are rugged industrial buttons to trigger any action on a computer. Perfect for CNC router, machine control on any computer driven process, or any application where a remote pendant control makes an operator safer and more efficient.

Specifications

Dimensions	2"(50mm) high x 2.7"(68mm) wide
Length	4 Button: 7.9"(20cm) 6 Button: 10.2"(26cm) 8 Button: 12.6"(32cm)
Weight	4 Button: 0.6lb (272g) 6 Button: 0.75lb (340g) 8 Button: 0.95lb (431g)
Actuation Force	Approx. 27 oz (770 g)
Connector Type	HD15 female
Mounting	0.15" (3mm) dia hole in molded tang
Voltage	Less than 32 volts
Current	Less than 1 Amp
Conductors	Rated for Severe Duty
RoHS	Compliant

Specifications subject to change without notice