


X-keys® XK-24 Android Specifications

for XK-0991-UMAK24-R



- 24 programmable keys
- Clear, removable key caps for applying and changing legends
- Includes programming software for Windows and Mac
- Free software development kits for developers
- Two color addressable backlighting (red and blue)

The X-keys XK-24 Android features 24 keys with independent backlighting. MacroWorks 3.1 software for Windows combines ease of programming with a wide and flexible range of options. P.I. Engineering's Pi3 firmware supports direct communication for the software developer and our new reflector feature sends messages to even the most reluctant software. The XK-24 Android may also be configured as a standalone USB keyboard with macros programmed in onboard non-volatile memory.

Free software development kits support all input and output data. Our SDK includes examples for C#, C++, and VB.NET and a separate SDK for Linux. Unique unit ID supports multiple units on the same system.

Specifications

Operating System	Use: Any OS via USB HID Programming: Windows XP through 10, Mac OS X 10.4 through 10.10
Free Programming Software	Windows: MacroWorks 3.1 Android: X-keys Android
Free Software Development Kits	Windows (C++, C#, VB.NET), Linux (C++), Android (Java), raw HID (any language/OS)
Emulation Modes	HID keyboard, HID mouse, HID game controller
Switch Type	Full-travel rubber dome, carbon on gold contacts, guaranteed for over 1 million operations
Number of Keys	24 single keys, 1 programming button
Actuation Force	Approx. 2.5 oz (72g) break-over, approx. 1.5 oz (42g) hold
Keycaps	0.625" (16mm) sq.; relegendable with Cherry MX compatible stem
Key Spacing	0.75" O.C.
Optional Keys	2x1, 1x2, 2x2, and 1x1 blocker
Backlighting	1 blue and 1 red addressable LED under each key
Connector	Wired USB 2.0 standard "A" plug
Cord Length	56" (1.42 m)
Dimensions	5.8" x 3.8" x 0.94" (147mm x 97mm x 24mm)
Weight	10 oz. (285 g)
USB type	USB 1.1 (compatible through 3.0)
Power Source	USB port, nominal voltage = 5 vdc
Power Consumption	No backlight: 18 mA , Blue backlight full: 38 mA, Red backlight full: 57 mA, All backlights: 75 mA
Temperature Range	-20 to 60 C
Memory Capacity	Each key is allocated 3 characters with a pool of 1000 additional keystrokes available to any keys that require additional characters
Memory Type	EEPROM, non volatile memory (X-keys retains memory for over 200 years)
Environmental Rating	IP 40, typical indoor office environment
Certifications	FCC class B, CE, RoHS, WEEE compliant

Specifications subject to change without notice

P.I. Engineering, Inc.
101 Innovation Parkway | Williamston, Michigan 48895-1663
Phone: (517) 655-5523 | Fax: (517) 655-4926
E-mail: tech@xkeys.com | Web: www.xkeys.com

