


# X-keys® XK-24 Black & White Specifications

for XK-1483-UABK24-R



- 24 programmable keys
- Clear, removable key caps for applying and changing legends
- Includes programming software for Windows and Mac
- Free software development kits for developers
- Two color addressable backlighting (red and blue)

The X-keys XK-24 Black & White features 24 keys with independent backlighting and a black case. MacroWorks 3.1 software for Windows and ControllerMate software for Mac OS X combine ease of programming with a wide and flexible range of options. P.I. Engineering's Pi3 firmware supports direct communication for the software developer and our new reflector feature sends messages to even the most reluctant software. The XK-24 may also be configured as a standalone USB keyboard with macros programmed in onboard non-volatile memory.

Free software development kits support all input and output data. Our SDK includes examples for C#, C++, and VB.NET and a separate SDK for Linux. Unique unit ID supports multiple units on the same system.

## Specifications

<b>Operating System</b>	Use: Any OS via USB HID   Programming: Windows XP through 10, Mac OS X 10.4 through 10.10
<b>Free Programming Software</b>	Windows: MacroWorks 3.1   Mac: ControllerMate for X-keys
<b>Free Software Development Kits</b>	Windows (C++, C#, VB.NET), Linux (C++), Android (Java), raw HID (any language/OS)
<b>Emulation Modes</b>	HID keyboard, HID mouse, HID game controller
<b>Switch Type</b>	Full-travel elastomer dome, carbon on gold contacts, guaranteed for over 1 million operations
<b>Number of Keys</b>	24 single keys, 1 programming button
<b>Actuation Force</b>	Approx. 2.5 oz (72g) break-over, approx. 1.5 oz (42g) hold
<b>Keycaps</b>	0.625" (16mm) sq.; relegendable with Cherry MX compatible stem
<b>Key Spacing</b>	0.75" O.C.
<b>Optional Keys</b>	2x1, 1x2, 2x2, and 1x1 blocker
<b>Backlighting</b>	24 white addressable LED under each key
<b>Connector</b>	Wired USB 3.0 standard "A" plug
<b>Cord Length</b>	118" (3 m)
<b>Dimensions</b>	5.8" x 3.8" x 0.94" (147mm x 97mm x 24mm)
<b>Weight</b>	12 oz. (340 g)
<b>USB type</b>	USB 1.1 compatible through 3.0 Type-c with adapter
<b>Power Source</b>	USB port, nominal voltage = 5 vdc
<b>Power Consumption</b>	No backlight: 18 mA, Blue backlight full: 38 mA, Red backlight full: 57 mA, All backlights: 75 mA
<b>Temperature Range</b>	-20 to 60 C
<b>Memory Capacity</b>	Approximately 21,000 keystrokes or commands in onboard memory
<b>Memory Type</b>	EEPROM, non-volatile memory (X-keys retains memory for over 200 years)
<b>Environmental Rating</b>	IP 40, typical indoor office environment
<b>Certifications</b>	FCC class B, CE, RoHS, WEEE compliant

Specifications subject to change without notice

P.I. Engineering, Inc.  
101 Innovation Parkway | Williamston, Michigan 48895-1663  
Phone: (517) 655-5523 | Fax: (517) 655-4926  
E-mail: tech@xkeys.com | Web: www.xkeys.com

